

PRODUCT INFORMATION

A



SPECIAL DESIGN

Depth of this inserts is only 35 cm, therefore they are recommended for shallow casings that save space.

EASY INSTALLATION

Double adjustment of the feet height (smooth and step up to +14 cm).
Cast iron out flue movable 360°.
Possibility of changing the direction of door opening in S models.

EASY TO OPERATE

Fireplace without grate allows cleaning with vacuum ash cleaner.
Inserts available with a guillotine door.

QUALITY

Insert made of high-quality P265GH boiler steel, which is resistant to continuous operation at high temperature. Reinforced door profile.
New guillotine mechanism with service access.

REPEATABILITY

Production use a modern machine park:
welding robots, press brakes, laser cutters.

ECOLOGY

Meet strict emission standards and the ECODESIGN directive, thanks to the use of afterburning system and two deflectors (steel and ceramic).

MODERNITY

DEKOR printed glass as standard.

SAFETY

The innovative ventilated handle protects against scalding.

CONTROL

The built-in four-stage damper enables adjustment of the amount of air supplied

Nominal power [kW]	7,6
Heating load range [kW]	4-10
Thermal efficiency [%]	77
CO emission (by 13% O ₂) [g/m ³]	0,719
Dust emission [g/m ³]	0,036
Average fuel consumption [kg/h]	2,3
Recommended active area of outlet grids [cm ²]	560-640
Recommended active area of inlet grids [cm ²]	320-520
Dimensions of the glass [mm]	590x430
External dimensions [mm]	701x1313x419
Maksimum log lenght [mm]	330
Flue diameter [mm]	160
Air intake diameter [mm]	125
Weight [kg]	165
Efficiency coefficient	102,7
Energy class	A

ADDITIONAL OPTIONS:

masking frame 4/4

