

## PRODUCT INFORMATION



### ECONOMY

Attractive price thanks to simplified construction.  
Available models with standard doors only.

### QUALITY

Inserts made of high-quality P265GH boiler steel, which is resistant to continuous operation at high temperature.  
A reinforced door profile is used.

### REPEATABILITY

Production use a modern machine park:  
welding robots, press brakes, laser cutters.

### ECOLOGY

Inserts meet restrictive emission standards and the ECODESIGN directive, thanks to the use of afterburning system and two deflectors.

### EASY OPERATION

Easy cleaning thanks to cast iron grate with a removable ash container.

### CONTROL

The built-in air intake with throttle enables adjustment of the amount of fresh air supplied.

### MODERNITY

Stylish black handle and printed Decor glass as standard.

Nominal power [kW]	11,0
Heating load range [kW]	5,5-14
Thermal efficiency [%]	75,5
CO emission (by 13% O <sub>2</sub> ) [g/m <sup>3</sup> ]	0,873
Dust emission [g/m <sup>3</sup> ]	0,037
Average fuel consumption [kg/h]	3,5
Combustion gas temperature [°C]	284
Recommended active area of outlet grids [cm <sup>2</sup> ]	770-880
Recommended active area of inlet grids [cm <sup>2</sup> ]	440-720
Dimensions of the glass [mm]	680x430x347
External dimensions [mm]	752x903x458
Maksimum log lenght [mm]	350
Flue diameter [mm]	180
Air intake diameter [mm]	125
Weight [kg]	109
Efficiency coefficient	100,5
Energy class	A

### ADDITIONAL EQUIPMENT:

heat radiators, steel out flue, adjustable feet (+4 cm)

### ADDITIONAL OPTIONS:

masking frame 4/4

